



Elvatech

Advanced XRF equipment and solutions

**DESIGNED FOR
HIGH-ACCURACY
ANALYSIS OF
PRECIOUS METALS
AND JEWELRY**

ElvaX
Jewelry Lab



ElvaX Jewelry Lab is aimed on high-accuracy analysis of jewelry and precious metals. Measurement process only takes several seconds. The result is shown in both percent share and karats. ElvaX Jewelry Lab is also capable of detecting coatings and nonstandard alloys. This instrument can be operated either using the embedded computer with the high-resolution touchscreen display, or using a PC with ElvaX™ software installed.

ACCURACY

Analysis accuracy of precious metals and jewelry is better than 0,1%

SPEED

The whole measurement process takes just several seconds

COMPLETENESS

Integrated computer, high-accuracy scales, printer and a rechargeable Li-ion battery

The integrated CCD camera makes it possible to target the required spot of the sample undergoing analysis.

Automatic collimator changer allows you to select the required measurement spot diameter.



Precious Alloys

5/27/2013, 1:19 PM SSS-7

14.0K Gold
Plating not detected
3.27 g

Au: 58.51 ± 0.04%
Cu: 33.31 ± 0.04%
Ag: 8.18 ± 0.03%



< **START** >



- ✓ High speed and accuracy
- ✓ Intuitive interface
- ✓ Autonomous operation as well as connected to a PC
- ✓ Coatings detection
- ✓ Compact, doesn't take much space on a desk or a counter
- ✓ Leaded glass to keep analyzed items always in sight
- ✓ Customer display



14 KARATT GOLD ANALYSIS RESULTS

	Au	Ag	Cu
1	58.55	8.21	33.24
2	58.59	8.18	33.23
3	58.63	8.2	33.17
4	58.6	8.16	33.24
5	58.56	8.19	33.25
6	58.61	8.22	33.17
7	58.64	8.18	33.18
8	58.58	8.17	33.25
9	58.59	8.24	33.17
10	58.63	8.16	33.21
Average	58.6	8.19	33.21
Std. deviation	0.03	0.03	0.04

Digital X-Ray Source digiX-40

Anode: W

Voltage: 40 kV

Current: 200 uAmp

Power: 4 W

5 position collimator changer from 1 to 10mm

X-Ray Detector

Type: Fast SDD (optional Si-PIN)

Area: 25 mm² (6 mm² for Si-PIN)

Energy resolution: 140 eV (165 eV for Si-PIN) at Mn Ka

Electronics

DPP: proprietary DAS (Dynamically Adaptive Shaping) type

MCA: 4096 channels

General

Dimensions: 280 x 385 x 200 mm

Analytical chamber: 185 x 212 x 90 mm

Weight: 7 kg

Power supply: 90 – 240 V, 50/60 Hz

Power consumption: 40 W

Battery: 6 hours continuous operation

Software

Operating system: Windows EC

Analysis algorithm: Fundamental parameters (FPA)

Connectivity

Data transfer: 2 USB ports, Micro SD, Ethernet

Data input: Keyboard and mouse can be connected for data input

Elvatech Ltd.

50 Mashynobudivna str.,

Kyiv 03680, Ukraine

Phone: +38 (044) 599-11-43

Fax: +38 (044) 406-65-83

E-mail: office@elvatech.com

www.elvatech.com