

## HERCULES EX

**EXPLOSION PROOF UV INSPECTION LIGHT** 



PREVENTS
LOSS OF LIFE



PROTECTS
YOUR ASSETS





Hercules Ex has successfully completed all tests leading to the *ATEX certification* for Group II, Zone II (Cert. No. ITS17ATEX402144), *NFPA 70 Article 500* for Class I (divisions II locations), the *Salt Fog Test* as per military standard 810F and the *Explosive Atmosphere Test* as per military standard 810G. This unique product complies with *ASTM E3022-15*, *Rolls-Royce RRES 90061* and *Airbus AITM6-1001*.

Four UV LEDs

≈ 4 000 μW/cm<sup>2</sup>

Battery Operated

Labino Article Number: L3000







## **TESTED TO COMPLY WITH**

		Initial UV Intensity* (µw/cm²)	ASTM E3022-15 Standard	ROLLS-ROYCE RRES 90061 Specification	AIRBUS AITM6-1001 Testing Method
GX SERIES – OVERHEAD LIGHT					
10.000	GX Orion REMOTE	I 500 – 7 000	/		
	GX Orion UV & WH	≈ 7 000	/		
	GX Orion UV	≈ 4 500	/	1	1
	GX Orion PLC	I 500 – 7 000	✓		
BB SERIES – HANDHELD LIGHT					
	BB Helios	≈ 8 500	<b>✓</b>		
	BB Ikaros	≈ 4 000	<b>✓</b>	✓	✓
MB SERIES – HANDHELD LIGHT					
	MB Hercules Ex	≈ 4 000	/	<b>✓</b>	✓
	MB Zeus	≈ 4 000	<b>✓</b>		✓
	MB Hermes	≈ 4 000	✓	✓	✓
	MB Zeus with Athena	≈ 4 000	/		<b>√</b>
	MB Hermes with Athena	≈ 4 000	/	1	1
	MB Iris	≈ 4 000	/	1	1
	MB Poseidon		В	Blue Light (450 nr	n)
UVG SERIES – FLASHLIGHT / HEADLIGHT					
	UVG3 MIDLIGHT	≈ 8 000	✓		
	UVG3 FLOODLIGHT	≈ 3 000	✓		<b>✓</b>
	UVG5 MIDLIGHT	≈ 8 000	/		
	UVG5 FLOODLIGHT	≈ 3 000	/		1

<sup>\*</sup> At a distance of 38cm (15 inches)